


| Prof.(m) | N(colpi p) | Rpd(kg/cm ²) | N(colpi r) | asta | Prof.(m) | N(colpi p) | Rpd(kg/cm ²) | N(colpi r) | asta |
|-------------|------------|--------------------------|------------|------|-------------|------------|--------------------------|------------|------|
| 0.00 - 0.10 | --- | --- | ---- | 1 | 0.70 - 0.80 | 12 | 43.2 | ---- | 1 |
| 0.10 - 0.20 | 8 | 28.8 | ---- | 1 | 0.80 - 0.90 | 11 | 38.1 | ---- | 2 |
| 0.20 - 0.30 | 8 | 28.8 | ---- | 1 | 0.90 - 1.00 | 10 | 34.6 | ---- | 2 |
| 0.30 - 0.40 | 10 | 36.0 | ---- | 1 | 1.00 - 1.10 | 11 | 38.1 | ---- | 2 |
| 0.40 - 0.50 | 17 | 61.2 | ---- | 1 | 1.10 - 1.20 | 20 | 69.2 | ---- | 2 |
| 0.50 - 0.60 | 20 | 72.0 | ---- | 1 | 1.20 - 1.30 | 50 | 173.1 | ---- | 2 |
| 0.60 - 0.70 | 20 | 72.0 | ---- | 1 | | | | | |



- PENETROMETRO DINAMICO tipo : DL-30 (90°)
 - M (massa battente)= 30.00 kg - H (altezza caduta)= 0.20 m - A (area punta)= 10.00 cm² - D(diam. punta)= 35.70 mm
 - Numero Colpi Punta N = N(10) [$\delta = 10$ cm] - Uso rivestimento / fanghi iniezione : NO